


Référence	Longueur 'L'	Dilatation (à 200°C)	Collier	Puissance (Watts)	T/C
DG001001.R	56mm	0.14mm	BF021021	240	MT020019
DG001002.R	74mm	0.19mm	BF021022	240	MT020021
DG001003.R	88mm	0.23mm	BF021023	400	MT020020
DG001004.R	106mm	0.29mm	BF021024	400	MT020020
DG001005.R	124mm	0.34mm	BF021025	400	MT020022
DG001006.R	142mm	0.40mm	BF021026	400	MT020021
DG001007.R	160mm	0.45mm	BF021027	610	MT020021
DG001008.R	178mm	0.51mm	BF021028	610	MT020023
DG001009.R	196mm	0.56mm	BF021029	610	MT020022
DG001110.R	223mm	0.64mm	BF021030	690	MT020023
DG001111.R	250mm	0.72mm	BF021031	690	MT020023

Indice	Date	Désignation			
					
ZA du PONT de l'ANE 42650 St JEAN BONNEFONDS TEL: 04.77.49.36.46 FAX: 04.77.33.46.00 e-mail: fastheat@fastheat.fr web: www.fastheat.fr					
		Ref.	Qté.	Designation / Catalog No.	
Nomenclature					
A3	Ech: 1,000	Date: 02-Apr-20	Dess. BC		
Description		Buse DG Pinpoint tête renforcée avec anneau de réduction			
Tol. Générale: JS13 js13		Emp.	Vol.	Client FAST HEAT	
Matiere		Verif.	No. Offre	No. Fab	DG