



Référence	Longueur 'L'	Dilatation (à 200°C)	Collier	Puissance (Watts)	T/C
SV370002.R	88.98mm	0.22mm	BF370000	400	MT020021
SV370005.R	101.68mm	0.26mm	BF370001	400	MT020021
SV370008.R	114.38mm	0.30mm	BF370002	610	MT020020
SV370011.R	127.08mm	0.34mm	BF370003	610	MT020022
SV370014.R	139.78mm	0.38mm	BF370004	610	MT020022
SV370017.R	152.48mm	0.41mm	BF370005	690	MT020022
SV370020.R	177.88mm	0.49mm	BF370006	690	MT020021
SV370023.R	203.28mm	0.57mm	BF370007	690	MT020023
SV370026.R	228.68mm	0.64mm	BF370008	950	MT020024
SV370029.R	254.08mm	0.72mm	BF370009	950	MT020023
SV370032.R	279.48mm	0.80mm	BF370010	950	MT020023

Indice	Date	Désignation				
<p>ZA du PONT de l'ANE 42650 St JEAN BONNEFONDS TEL:04.77.49.36.46 FAX:04.77.33.46.00 e-mail: fastheat@fastheat.fr</p>		Ref.	Qté.	Designation / Catalog No.		
		Nomenclature				
		A3	Ech:1,000	Date:08-Apr-20	Dess. BC	
		Description		Buse SV9 Tête renforcée Type 3		
Tol.Générale:JS13 js13		Emp.	Vol.	Client FAST HEAT		
Matiere		Verif.	No.Offre	No.Fab	SV9-R	